

• \* = STANDARDS LICENSED TO AS/NZS 3718

<i>Description</i>	<i>Operating Criteria</i>	<i>Model</i>	
Basin Tap Heavy Pattern.	Compression Washer Suitable all pressures	111S *	
Basin Tap Light Pattern.	Projection 85 mm	211S *	
As above. With Aerator thread on outlet.	M22 outlet	203SD	
Basin Tap Heavy Pattern Elbow action Ceramic Disc.	Ceramic Disc 1/4 Turn- Handed left & right 150mm Lever	503.21 *	
Sink Tap extended, flanged.	Projection 135mm	201S	
As above, with aerator.	Projection 135mm	201SA	
As above, with Aerator thread on spout.	Projection 135mm M22 Thread	201SD	
Bib Tap male 15mm. Bib Tap male 20mm.	Projection 84mm Projection 112mm	106S x15 * 106S x 20 *	
Bath Tap extended, loose flange 20mm (pictured).	Projection 155-175	106S/059 x 20 *	
Tub Tap, flanged female.	Projection 105mm	207S	
As Above With aerator thread on spout.	Projection 105mm M22 Thread	207SD	
As above with aerator.	Projection 105mm	207SA	
Sink Tap extended, flanged with 15mm female socket outlet.	Projection 135mm	201SC	
Washing machine conversion set 15mm flanged inlet	Projections 40mm 135mm	213S	

• \* = STANDARDS LICENSED TO AS/NZS 3718

Description	Dimensions	Model	
Hose Tap polished CP, male less union 15mm.	Projection 84mm	107EC*	
As above but flanged female inlet.		107ECF	
Shower Tap concealed with loose flange 15mm FxF.	70mm	128S-15*	
Shower Tap concealed with loose flange 20mm FxF.	84mm	128S-20*	
Stop Tap 15mm.	70mm	126S*	
Washing Machine Tap flanged 15mm x 20mm.	Projection (outlet) 35mm	209S	
Monobloc Sink Faucet - Swivel Spout. With flexible connectors 15mm.  Other spouts available on request.	Projection 175mm Height (outlet to bench) 239mm	296S*	
Sink Faucet 155-200mm adjustable centres. Male inlets 15mm.	Projection 260mm	166/041*	
Bench Mount 155-200mm adjustable centres. Male inlets 15mm. Available with Ceramic Disc ¼ turn and 150mm levers.	Projection 165 - 215mm	171/041*  521/21*	
Sink Pillar Tap - Swivel Spout 15mm.	Projection 190mm	115/046*	