


DRINKING FOUNTAINS



- FLOW RATE AT 400 kPA 25 L/M (UNREGULATED), 6 L/M (REGULATED)
 - RECOMMENDED WORKING PRESSURE 20 - 1200 kPA
 - SELF CLOSING TAPS MADE IN DEZINCIFICATION RESISTANT BRASS TO AS3718
 - VANDAL PROOF FEATURES
 - SUITABLE FOR USE IN SCHOOLS, MUNICIPAL AND OTHER GENERAL PUBLIC AREAS IN THE INTEREST OF WATER CONSERVATION
- AVAILABLE WITH: (C) CAM ACTION (L) LEVER ACTION (B) PUSH BUTTON EXCEPT BUB290



<i>Description</i>	<i>Dimensions</i>	<i>Model</i>	
Wall mounted Fountain 15mm female loose nut.	A) 180mm C) 130mm	BUB 205	
Upright Fountain 15mm female.	C) 160mm	BUB 206	
Wall Fountain with Stainless Steel Bowl 15mm female.	A) 200mm C) 210mm Bowl- 310 Ø	BUB 218	
Pedestal Fountain with Stainless Steel Bowl 15mm female (Available with white powder coated stanchion).	C) 785mm Bowl 310 Ø	BUB 215	
Bubbler Outlet (Push Button Only) 10mm female (15mm inlet adaptor available).	C) 90mm	BUB 290	
Heavy Duty Glass Filler 15mm female.	A) 80mm B) 250mm C) 300mm	BUB 281	
Wall mounted Fountain 15mm female.	A) 110mm	BUB 224	

A=Projection , B=Distance to bench top , C=Height