

INFRA-RED URINAL VALVES



<i>Description</i>	<i>Operating Criteria</i>	<i>Model</i>	
<p>Wall mounted, white epoxy coated infra-red urinal flushing valve. Programmable with pre-rinse function. 15mm connections 10IPm Safety lock in case of prolonged Leakage or damage. Shutdown in case of battery wear.</p> <p>Flush pipe not included.</p>	<p>A) 125mm B) 130mm</p> <p>6v Lithium battery 300,000 operations.</p> <p>Pressure 30-700 kPa</p>	<p>SENSAO 8200</p> <p>In line connection ref. 55300</p> <p>Right angle connection ref. 55310</p>	
<p>Wall mounted, right angle infra-red urinal flushing valve CP.</p> <p>As above.</p> <p>Includes flush pipe.</p>	<p>A) 185mm B) 60mm</p> <p>6v Lithium battery 300,000 operations.</p>	<p>SENSAO 8400</p>	

<i>Description</i>	<i>Operating Criteria</i>	<i>Model</i>	
<p>Radar Control Programmer for urinals allows settings of sensors without expensive removal of urinal bowls. Total solution for vandalism, Hygiene and water economy. On wall and built in installation options available. Extra safe low voltage, easily adjusted. Consists of 763U Radar Unit, solenoid valve with isolator and programmer.</p>	<p>Detection Range - 400mm - 600mm - 800mm Adjustable settings Power consumption - 12vac Frequency - 5.8Ghz +/- 75mHz Transmitting power <5mW Duty flush - 3 sec Duty flush cycle 12,24,36 Hours</p>	<p>RADA Meltronic MC 763U</p>	