






HEAVY DUTY. DEZINCIFICATION RESISTANT BRASS

Check Valve + Line Strainers



S.A.B.S APPROVED

| Description | Operating Criteria | Model | |
|---|--------------------|-------|---|
| Check Valve Swing Type. 15 - 50mm. BSP taper thread BS5154 Use in ascending or horizontal pipe runs ONLY | Rated to 2000kPa | 1022 |  |
| Cast brass in line strainer with BSP parallel Thread. Stainless steel double mesh basket 15,20x25mm | Rated to 2000kPa | 1050 |  |

BALL VALVE


| Description | Operating Criteria | Model | |
|---|---|--|--|
| Filter Ball valve 'T' handle, Stainless mesh filter, C.P. Brass ball C.P. Brass body BS5154, DN20 Available 15,20 x 25mm Sizes. | Rated to 2000kPa | 616/1/F  |  |
| ½' (15mm) M+F Original 'Ballofix®' valve, Complete with detachable handle. SAQS Water-mark and international approvals. Dezincification resistant brass. AUST. STANDARDS SPEC.012. LICENCE NO.W182 | Working pressure (fluid) up to 6000kPa (Working temperature from +5° +0 +120°C) | 39000 |  |

BALL FLOW INDICATORS

| Description | Operating Criteria | Model | |
|---|--|---|---|
| Glass domed valve with ball to indicate liquid flow. Available in 1/2", 3/4", 1" sizes Spinner type indicators also available 15mm-50mm | Max pressure 700 kPa, High pressure and high temperature on request. | Rada BFI  |  |








GATE VALVES

SABS 776-1975, STANDARDS LICENCED AS/NZS 1628

| Description | Operating Criteria | Model | |
|---|--|---------|---|
| 'Prestex' Cast DZR Brass Fullway Gate Valve to SABS 776-1975, Class 8, AS/NZS1628, with non-rising spindle and guided wedge. BSP Parallel thread female end connections Cast aluminium handwheels. BS5154, PN20 Sizes: -10mm (3/8") -15mm (1/2") -20mm (3/4") -25mm (1") -32mm (1 1/4") -40mm (1 1/2") -50mm (2") -65mm (2 1/2") -80mm (3") -100mm (4") Available with 'T' handle Tested to 2100kPa | Suitable for steam working pressures to 880 kPa at 175°C and hydraulic working pressures up to 1600 kPa (non-shock) Use as isolating valve only | 1008MAL |  |


HOSE TAPS, BIB TAPS AND FITTINGS

DEZINCIFICATION RESISTANT
BRASS. S.A.B.S. APPROVED.
STANDARDS LICENCED TO AS/NZ 3718

| <i>Description</i> | <i>Dimensions</i> | <i>Model</i> | |
|---|--|------------------|---|
| Bib Tap unpolished 15mm male inlet | Projection) 84mm | 100-15 |  |
| 20mm male inlet BS5412 | Projection) 105mm | 100-20 | |
| Hose Bib 15mm male inlet 20mm male outlet BS5412 | Projection) 84mm | 108-15 |  |
| 20mm male inlet 20mm male outlet BS5412 | Projection) 105mm | 108-20 | |
| Hose Bib Tap lockshield 15mm male inlet 15 / 20mm (pictured right) male inlet Tamperproof cover. Supplied with key and brass hose union nut and tail. BS5412 Chrome plate available on request. 20/20mm | Projection) 84mm | 108LK-15 |  |
| | Projection) 105mm | 108LK-20 | |
| Hose Union Nut & Tail. For 15mm x 20mm hose tap 20mm female hose union, brass. | $\frac{3}{4}$ " BSP female nut, 15mm (OD) | 080-20-15 |  |
| | $\frac{3}{4}$ " BSP female nut, 20mm (OD) | 080-20-20 | |
| Hose tail 20mm male thread. | $\frac{3}{4}$ " BSP male 15mm tail (OD) | 079 |  |
| Angle hose Bib integral with dual check valve and test point to BS101-2. 15mm male inlet. Dezincification resistant brass CP | Projection) 55mm  | 667/DR/H |  |


ISOLATION VALVE

DEZINCIFICATION RESISTANT BRASS
STANDARDS LICENCED TO AS/NZ 3718

| <i>Description</i> | <i>dimensions</i> | <i>Model</i> | |
|---|------------------------|-----------------|---|
| Isolation Valve. 15 and 20mm female with adjustable wall flange. Provides tamperproof setting of water. Supplied without key. | W) 70mm | 128LK-15 |  |
| | W) 84mm | 128LK-20 | |
| Key for Lockshield Taps & Isolation Valve | Loose Key C-084 | | |

STOP TAPS

DEZINCIFICATION RESISTANT
BRASS. S.A.B.S. APPROVED.
STANDARDS LICENCED TO AS/NZ 3718

| <i>Description</i> | <i>dimensions</i> | <i>Model</i> | |
|--|--------------------------------|---|---|
| Stop Tap Female. 15mm, 20mm, 25mm BS5412. Larger sizes on request. | W) 70mm W) 84mm W) 102mm | 121 - 15 121 - 20 121 - 25 |  |
| Stop Tap Female lockshield. 15mm and 20mm. Tamperproof stop tap supplied with key. | W) 70mm W) 84mm | 121LK-15 121LK-20 | |