




PRESSURE REGULATING VALVES

DESBORDES

BRONZE BODIES . SUITABLE FOR WATER UP TO 80°C

FULLY ADJUSTABLE - SILENT OPERATION.

NO MAINTENANCE , SCALE AND DIRT PROOF. DOWNSTREAM PRESSURE CONTROLLED WHETHER THERE IS FLOW OR NOT.

<i>Description</i>	<i>Operating Criteria</i>	<i>Model</i>	
'Junior' adjustable pressure regulating valve from 100-550 kPa. Female connections ¼". Pressure gauge connection and drain plug under base 15 & 20mm Factory set to 300 kPa.	Maximum inlet pressure 1600kPa (230 psi) Max flow 15mm 50 lpm Max flow 20mm 72 lpm Max temp 80°C	7 BIS	
Pressure regulating valve adjustable from 50-700 kPa. Female connections. Unset. 15mm - 50 mm Fitted with pressure gauge connection on outlet.	Maximum inlet pressure 2500 kPa (360 psi) Max temp 80°C	10 BIS	
Pressure regulating valve adjustable from 50-700 kPa Flanged connections - 65mm to 100mm. Unset. Fitted with pressure gauge connection on outlet.	Maximum inlet pressure 2500 kPa (360 psi) Max temp 80°C	10 TER	
Pressure regulating valves adjustable from 50-550 kPa. Pressure gauge connection and drain plug under base. Factory Set to 300 kPa. 15 & 20mm	Maximum inlet pressure 2500 kPa (360 psi) Max flow 15mm 80 lpm	11 BIS	
Pressure regulating valve for outlet pressures 0-100 kPa. 20mm female connections. Pressure gauge connection and drain plug under base.	Max temp 80°C	11 BIS RCBP	

DESBORDES

PRESSURE REGULATING VALVES HAVE APPROVALS UNDER THE FOLLOWING NATIONAL STANDARDS

- GERMANY - DIN STANDARDS
- BELGIUM - L.E.I.G.C. LIEGE
- SWITZERLAND - CONTROL O.D.E.Z. ZURICH
- U.K - UK WFBS LISTED WRC
- CANADA - MINISTRY OF HOUSING APPROVED
- NORWAY - CIRTIF. M.T.F. OSLO
- PANAMA - CIRTIF. I.D.A.A.N
- SINGAPORE - P-U-B 1989
- FRANCE - NORM. P. 43006