

TIME FLOW BASIN TAPS




OPERATING PRESSURES - MIN 0.2 BAR , MAX 7 BAR.

VANDAL RESISTANT TIMED FLOW TAPWARE WITH ADJUSTABLE FLOW RATES. NON-CONCUSSIVE SHUT OFF. TIMES ARE APPROXIMATE.

TO WITHSTAND CONSTANT HOT WATER TO 70°C. NF - A - 51105 AND NF - A - 53703

Description	Dimensions	Model	
Push button basin tap. Specify 7 or 15 second, red or blue.	A) 121mm B) 59mm C) 80mm	605*	
Push button basin tap. 7 second, Red or blue.	A) 110mm B) 50mm C) 82mm	66	
Lever operated basin tap. 15 sec. Comes with red & blue insert into black knob.	A) 121mm B) 59mm C) 172mm	705	
Push button bib tap. 7 or 15 sec., red or blue.	A) 65mm (spout) 96mm (button)	504*	
Push button bib tap 15 second, red or blue	B) 45mm	56	
Lever operated bib tap 15 sec. Comes with red & blue insert into black knob. Extension pieces available.	A) 65mm (spout) 190mm (knob) B) 45mm	704	
Duct mounted tap with through-the-wall push button. Please specify wall thickness. 7 or 15 sec.	0-15mm 15-200 mm 200-300 mm	512TC	
Push button basin tap. Adjustable time delay. Red or blue.	A) 127mm B) 66mm C) 127mm	2000*	
Push button bib tap. Adjustable time delay. Red or blue.	A) 116mm from wall	2010	
Push button mixer tap with temperature control lever at rear. Adjustable time delay. With isolators, filters, flexible hoses and non-returns.	A) 127mm B) 127mm	2020	
Push button mixer tap with temperature control lever at right. With isolators, filters, flexible hoses and non-returns. 15 sec.	A) 121mm B) 69mm C) 95mm	3000*	
Available with lever.	A)121 B)69 C)179	7000	



**  ** ALSO AVAILABLE: "S" VERSIONS OF ABOVE TAPS (EXCEPT 704/705). WATER RUNS ONLY WHEN HANDLE RELEASED

OPERATING CRITERIA: PRESSURES 20-700 kPA MAX HOT TEMP 90°C

* = STANDARDS LICENCED TO AS/NZ 3718

BASIN TAPS



Description	Dimensions	Model	
Push button mixing tap with stopcocks, filters and flexible pipes. 15 sec. Black plastic knob. Minimum pressure 100 kPa.	A) 123mm B) 67mm C) 143mm	S 4000 S	
As above. Chromed brass knob.		S 4000 S-BC	
Knee operated lever tap for under basins. 390mm total length. Longer versions on request. 15 sec.	A) 390mm	712	
Right angled version of above		712 A	
As above with basin mounted swivel spout (150mm) .		712/ SP020	

