




SHOWERS AND SHOWER FITTINGS


WALL ELBOWS

Description	Operating Criteria	Model	
CP/Brass Elbow. 15mm M x M.	All Pressures	3250	
CP/Brass Elbow. Light Pattern with loose flange 15mm M x M.	All Pressures	3280	


CHECK VALVE

Description	Operating Criteria	Model	
Chrome plate single check Anti-syphon Device. DZR Brass 15mm F x M.	Max Temp: 100°C Max Pressure: 1600 kPa	618	

STAINLESS STEEL HOSES


Description	Length	Operating Criteria	Model	
7mm Internal bore Stainless steel Braided hose 15mm FxF.	1.0m	High pressure	MIS 534	
As above.	1.5m	High pressure	MIS 535	
As above.	2.0m	High pressure	MIS 536	

SHOWER HOSES

Description	Length	Operating Criteria	Model	
Double ribbed CP brass, 9mm internal bore. Conical nut one end. 847E - 1.5 Available in gold.	1.2m 1.5m 2.0m 1.5m	All pressures	847E-1.2 847E-1.5 847E-2.0 847EG-1.5	
Plastic Coated , white or chrome 13mm internal bore. Conical nut both ends. Stainless steel reinforced.	1.25m	All pressures	RF4 CP RF4 WH	
Extra Heavy duty 8mm internal bore. CP Brass.	1.5m 2.0m	High pressure	RU525-1.5 RU525-2.0	
Extra Heavy duty 9mm internal bore.	1.5m 2.0m	All pressures	TA529-1.5 TA531-2	

WASH DOWN

SuperKlean

Description	Operating Criteria	Model	
Spray nozzle - anodised aluminium for hot Water washdown (Not for use with steam).	170kPa - 1000kPa / 93°C	150A - W (white cover) 150A - LO (blue cover)	
Stainless steel ½" hose-barb swivel adaptor to fit 150A. 360° Swivel to prevent hose kinking.		8-½-5	