


SINGLE POINT SHOWERS



TMV3 = A THERMOSTATIC MIXING VALVE WITH ENHANCED THERMAL PERFORMANCE COMPLYING WITH NHS (NATIONAL HEALTH SERVICES) U.K REQUIREMENTS FOR BATHING, SHOWERING, HANDWASH

ALL MIRA AND MEYNELL SINGLE POINT SHOWERS COMPLY WITH PERFORMANCE REQUIREMENTS G12.3.6 . ASG032 . 1 - 2002

Description	Operating Criteria	Model	
Built-in 15mm thermostatic mixer CP with concealing plate. Separate temperature & ceramic disc flow controls. Complete with strainers.	Nominally equal pressures 6-500 kPa. Max static 100 kPa. Max pressure loss ratio* 10:1 in favour of either supply.	Mira Excel B	
Exposed version of above.		Mira Excel	

*NOTE FOR THERMOSTATIC MIXERS: *PRESSURE LOSS RATIO* IS DETERMINED BY SUBTRACTING THE RESISTANCE OF THE OUTLET PIPEWORK FROM THE DYNAMIC PRESSURES OF THE HOT AND COLD WATER AT THE INLETS OF THE MIXING VALVE. THIS IS AT ITS EXTREME WHEN THE MIXING VALVE IS BEING USED AT ITS LOWEST FLOW RATE AND WHEN THE MAXIMUM INEQUALITY OCCURS IN THE PRESSURE OF THE HOT AND COLD WATER SUPPLIES.

