

# THERMOSCOPIC MIXERS



RADA THERMOSCOPIC VALVES MAINTAIN FULL THERMAL PERFORMANCE WITH A PRESSURE LOSS RATIO AS HIGH AS 10:1 COMPARED TO 5:1 FOR MOST CONVENTIONAL MIXING VALVES.

THERMOSCOPIC MIXERS FOR MULTIPLE OUTLETS - REQUIRES FLOW CONTROL AT OUTLET. INCLUDES BUILT-IN NON-RETURNS AND STRAINERS

ALL VALVES COMPLY WITH PERFORMANCE STANDARDS G12.3.6 , AS4032 . 1 - 2002

MANUFACTURED TO BS EN1111 AND BS EN1287

<p>For duct /under bench mounting, locked temp knob. Nickel Plated. Includes strainers and non-return valves 15mm. Flow rate 35lpm @ 200kPa.</p> <p>Approved for healthcare application. </p>	<p>Pressures 15-500 kPa Max pressure loss ratio* 10:1 For flow rates 3-35 l/min</p>	<p><b>215 dk</b></p>	
<p>Built in mixer for concealed mounting c/w stainless concealing plate. CP. Includes strainers and non-return valves 15mm.</p> <p>Approved for healthcare application. </p>	<p>As above</p>	<p><b>215 bc</b></p>	
<p>As above but with side entry and no concealing plate. CP. Includes strainers and non-return valves 15mm.</p> <p>Approved for healthcare application. </p>	<p>As above</p>	<p><b>215 oem</b></p>	
<p>For exposed mounting where pipework is exposed. CP. Includes strainers and non-return valves.</p> <p>Approved for healthcare application. </p>	<p>As above</p>	<p><b>Rada 215-t3 c</b></p>	
<p>25mm male inlets/outlet for surface, duct or panel mounting inlet adapter. Include strainers and non-return valves. Replaces Rada 17 &amp; Rada 20.</p> <p>Approved for healthcare application. </p>	<p>Flow rate 120lpm @ 500kPa</p>	<p><b>Rada 320 oem</b></p>	
<p>For surface mounting elbows include non-return valves, filters and integral isolating ball valves inlets and outlet 20mm.</p> <p>Approved for healthcare application. </p>	<p>As above</p>	<p><b>Rada 320cx</b></p>	
<p>For surface, duct or panel mounting. Includes Non return valves and strainers 32mm inlets and outlet.</p> <p>Approved for healthcare application. </p>	<p>Flow rate 200lpm @ 300kPa</p>	<p><b>Rada 425 ALNZ</b></p>	
<p>For surface mounting elbows incorporate non-return valves, filters and integral isolating ball valves. 25mm inlets and outlets.</p> <p>Approved for healthcare application. </p>	<p>150mm H 300mm W 200mm L</p>	<p><b>Rada 425cx</b></p>	