





# THERMOSTATIC MIXING TAP



TMV3 = A THERMOSTATIC MIXING VALVE WITH ENHANCED THERMAL PERFORMANCE COMPLYING WITH NHS (NATIONAL HEALTH SERVICES) U.K REQUIREMENTS FOR BATHING, SHOWERING, HANDWASH

DEZINCIFICATION RESISTANT BRASS

Description	Operating Criteria	Model	
<p>15mm Thermostatic Mixing Tap operates flow and temperature. Sequential mixer fitted with Strainers and flexible tails. For hand, wrist or elbow operation 180° Factory set at 41°C.</p> <p>The only TMV3 approved basin mixer on the market.</p> 	<p>Pressures: 10-1000 kPa Max pressure loss ratio* 10:1</p> <p>Projection) 110</p>	<p><b>Rada Thermo tap-3S - 100mm Lever</b></p> <p><b>Rada Thermo tap-3L - 150mm Lever</b></p>	
<p>15mm Thermostatic mixing valve with accurate temperature control and easy flow control for healthcare and commercial handwashing.</p> <p>complies with BS7942, BSEN1111 and BSEN1287.</p>	<p>Pressure 20 - 1000 kPa Max pressure loss ratio 10:1 Maximum flow rate 40l/min Height = 248</p>	<p><b>Rada Verve with Intermediate spout</b></p>	
<p>As Above.</p>	<p>Height = 380</p>	<p><b>Rada Verve with High neck spout</b></p>	
<p>As Above.</p>	<p>Measures 258 from top of mixer to bottom of spout</p>	<p><b>Rada Verve with Underslung spout</b></p>	