

TOILET FLUSHING VALVES



ALL COBRA FLUSHING VALVES BEAR THE SABS MARK (SABS 1420—1979)
CERTIFICATE OF APPRAISAL TO MEET NZBS-B2, G1 AND G12

WATERMARK LICENSED TO MP 52
SPEC 020 AND 021

<i>Description</i>	<i>Operating Criteria</i>	<i>Model</i>	
32mm Standard 'Flushmaster' CP. Back entry type, non-return valve, extendable inlet control stop and wall plate. Comprises flushvalve, bent flushpipe 335 x 140mm and rubber pipe connector.	Optimum 30-300 kPa inlet flow pressure. For Higher pressures, velocity parameters should be taken into consideration. Ideal for tank or mains supply.	FM1.100	
As above without flushpipe		FM1.000	
32mm Standard 'Flushmaster' CP. Back entry type with butterfly valve. Comprises flushvalve, wall flange, bent flushpipe 335 x 140mm and rubber pipe connector and wall plate.	As above.	FM2.100	
Top entry type	For top entry pans and sluice sinks	FM2.210	
As above without flushpipe.		FM2.000	
As above unpolished for concealed application.		KF1.104	
'Belva' Adaptor available for when replacing old low pressure valves. Fits 'Cobra Flushmaster' and 'Econoflush' valves. This enables retention of existing flushpipe. With washers. CP + Brass Stuart/Tanner inlet adaptor converts 'Cobra Flushmaster to P/C' male inlet. Brass.	To fit 40mm flushpipe	'Belva' Adaptor 20022-CP 20023-B Stuart/Tanner Adaptor 20025	
32mm Standard 'Flushmaster.' Duct mounted, with non-return valve, extendable inlet control stop. For rising, falling, or back entry. Comprises flushvalve, chrome plated push-button assembly, elbow, straight flushpipes and rubber pipe connector.	As above.	FM3.402	
As above without flushpipe.		FM3.400	
As above but with butterfly valve isolator. Side entry.		KF3.402	
32mm 'Econoflush' concealed front-access type, with butterfly valve. Right hand inlet. Comprises rough brass flushvalve, box with stainless steel front, vertical flushpipe 680mm, elbow, chrome plated flushpipe 280mm and rubber pipe connector.	As above In wall box: 105mm deep. 220mm high 190mm wide Cover plate: 250mm high 230mm wide	KF3.412	
20mm "Junior" , concealed front-access type, with ball-o-flo valve. Right hand inlet. Comprises flushvalve, box with stainless steel front, vertical flared flushpipe 760mm, elbow, chrome plated flushpipe 40mm Ø x 300mm and rubber pipe connector.	Optimum 150-500 kPa inlet pressure. In wall box as above	KF4.213	

ALL COBRA TOILET FLUSHING VALVES HAVE AN INTEGRAL VACUUM BREAKER AND NON-HOLD OPEN FEATURE TO PREVENT THE VALVE FROM RUNNING CONTINUOUSLY.