

# TOILET & URINAL FLUSHING VALVES



Description	Operating Criteria	Model	
<p>20mm 'Flushmaster Junior' Toilet Flushvalve. Duct mounted, with ball-o-flo valve. Left, right or rear entry. Comprises flushvalve, push-button assembly, vertical flared flushpipe 680mm, elbow, chrome plated flushpipe 40mm Ø x 450mm and rubber pipe connector.</p>	<p>Optimum 150-500 kPa inlet pressure.</p>	<p>FJ4.203</p>	
<p>Institutional version available of above. Includes Vandal resistant guide tube, Flush push button assembly with push rod and captive linkage.</p>	<p>Thru - the - wall (310mm max)</p>	<p>FJ4.203 PR</p>	
<p>20mm "Junior" concealed front-access toilet flushvalve, with ball-o-flo valve. Palm push button. Right hand inlet. 70mm 'Palm-Push' button. Comprises flushvalve, box with stainless steel cover, vertical flared flushpipe 760mm, elbow, chrome plated flushpipe 40mm Ø x 300mm and rubber pipe connector. Left hand inlet available on request.</p>	<p>In wall box: 65mm deep. 210mm high 210mm wide Cover plate: 235mm high 235mm wide</p>	<p>KF4-NZ1</p>	
<p>20mm flushmaster junior toilet flushvalve exposed-back entry . Comprises flushpipe 640mm x 140mm CP, rubber pan connector. and CP wall flange.</p>	<p>Optimum inlet pressure 150 - 500kPa Pipe "B"</p>	<p>FJ2.100</p>	
<p>20mm flushmaster junior toilet or Sluice flushvalve exposed-Top entry. Comprises flushpipe CP 470mm, rubber seat buffer, pan connector and CP wall Flange.</p>	<p>Optimum inlet pressure 200 - 500kPa Pipe "A"</p>	<p>FJ2.210</p>	
<p>20mm 'Flushmaster Junior' Urinal Flushvalve. Bright chrome plated, exposed type, with ball-o-flo valve and wall plate. Comprises valve and wall plate only with additional flow regulator for stall urinals. Flushpipe not included.</p>	<p>Optimum 30-500 kPa inlet pressure. Diaphragm operation.</p>	<p>FJ6.000</p>	
<p>20mm 'Flushmaster Junior' Urinal Flushvalve. Brushed chrome, duct mounted type, with ball-o-flo valve.  Comprises flushvalve, chrome plated push-button assembly and flushpipe 300mm.</p>	<p>As above</p>	<p>FJ8.102</p>	
<p>20mm male inlet 'Econoflush' Urinal Flushvalve. Front-access concealed type, with integral non-hold-open feature and ball-o-flo valve. Right hand entry.  Comprises flushvalve, front-access box with stainless steel cover and straight flushpipe 300mm.</p>	<p>As above In wall box: 105mm deep. 220mm high 190mm wide Cover plate: 250mm high 230mm wide</p>	<p>KF8.112</p>	
<p>20mm male inlet 'Econoflush' Urinal Flushvalve. Front-access concealed type, with integral non-hold-open feature and ball-o-flo valve. Right hand entry. 70mm 'Palm-Push' button. Comprises flushvalve, front-access box with stainless steel cover and 20mm outlet fitting. Left hand inlet available on request.</p>	<p>In wall box: 65mm deep. 210mm high 210mm wide Cover plate: 235mm high 235mm wide</p>	<p>KF8-NZ1</p>	